



# Heavy-duty 2" Insulated Sectional Door

Amarr® 2432

The Amarr 2432 features heavy-duty solid steel construction. Two tough steel skins and an advanced 4-step insulation system make the Amarr 2432 a strong and durable door.

The outer skin is made from 24-gauge steel and features a stucco embossment with shallow pencil grooves. The interior skin utilizes 27-gauge steel with stucco embossment.


The 4-step insulation system includes tongue and groove construction, CFC-free polystyrene insulation, weather-stripping, and a thermal break that provides a strong barrier from extreme heat and cold.



## CONSTRUCTION

**R-Value 9.05** Amarr 2432 FORMERLY 1000  
Heavy-duty, 2" 24-gauge steel

### TRIPLE-LAYER Steel + Insulation + Steel



**Track:** All Amarr doors are available with both 2" or 3" track in Standard Lift, High Lift, Vertical Lift, Low Headroom, and Follow the Roof Pitch. Custom track configurations are also available. For drawings and more information, please visit [www.amarr.com](http://www.amarr.com).

**Springs:** Torsion springs are oil tempered, helical wound and custom computed for each door for a minimum 10,000 cycle life. Optional springs are available up to 100,000 cycle life.

**Hardware:** Amarr hardware includes minimum 14-gauge galvanized steel hinges and 13-gauge galvanized steel track brackets. All rollers have minimum 10-ball bearings.

## SPECIFICATIONS

	Heavy-duty <b>Amarr 2432</b> formerly 1000
STEEL THICKNESS (Front/Back)	24-ga / 27-ga
PANEL DESIGN	Pencil Groove
STEEL EMBOSSMENT	Stucco
DOOR THICKNESS	2" (5.1cm)
CONSTRUCTION LAYERS	Triple
INSULATION <sup>1</sup>	Polystyrene
R-VALUE <sup>2</sup>	9.05
MINIMUM WIDTH	6'
MAXIMUM WIDTH	24' 2"
MINIMUM HEIGHT	7'
MAXIMUM HEIGHT	26' 1"
WIND LOAD <sup>3</sup> AVAILABLE	•
PAINT FINISH WARRANTY <sup>4</sup>	10 Years
WORKMANSHIP/HARDWARE WARRANTY <sup>4</sup>	1 Year

<sup>1</sup> Insulation has passed self-ignition, flamespread and smoke developed index fire testing.

<sup>2</sup> Calculated door section R-value is in accordance with DASMA TDS-163.

<sup>3</sup> It is your responsibility to make sure your garage door meets local building codes.

<sup>4</sup> For complete warranty details, visit [amarr.com](http://amarr.com) or contact your local Amarr dealer.

## PANEL OPTIONS



PENCIL GROOVE PANEL WITH STUCCO EMBOSSMENT

## WINDOW OPTIONS



24" X 12" INSULATED GLASS  
Available with either a black or white frame.



24" X 6" DOUBLE INSULATED  
ACRYLIC WINDOWS WITH BLACK FRAME

## COLORS

Amarr steel doors are pre-painted; for custom colors, exterior latex paint must be used. Visit [amarr.com](http://amarr.com) for instructions on painting. Actual paint colors may vary from samples shown.



WHITE



SANDTONE



COMMERCIAL GRAY



COMMERCIAL BROWN



## ENTRE/MATIC

**Entrematic**  
165 Carriage Court  
Winston-Salem, NC 27105  
800.503.DOOR  
[www.amarr.com](http://www.amarr.com)

FOR TECHNICAL  
QUESTIONS:  
1.866.366.4814



YOUR LOCAL AMARR DEALER: